REVISOES	DATA	PROJ.	VISTO
REVISION 1 INITIAL	24/04/2001	Norberto	NJSA
-REVISION 2 -C411 WAS 470u 16V -L201 WAS 10uH -R205 WAS 680 1/4W -IC101 WAS TDA9380 A169 -IC450/IC451 WAS TDA9855 A206 ADDED R882	29/05/2001	Norberto	NJSA
REVISION 3 R936 WAS 3K3	29/06/2001	Norberto	NJSA
Translated to English	11/07/2001	Norberto	NJSA

NOTES :

1- RESISTORS VALUES IN OHMS
K=10³ OHMS M=10⁶ OHMS
FUSE RESISTOR
LEADED RESISTORS
SMD RESISTORS

2- CAPACITORS VALUES IN FARADS
n=10⁻⁹ p=10⁻¹²
ELETROLITIC
LEADED
SMD

3 COMPONENTS IDENTIFIED WITH
SIMBOL ⚠ ARE SAFETY COMPONENTS. REPLACE THEM
WITH APROVED COMPONENTS BY REA.

4- TENSION INDICATED IN THE SEMICONDUCTORS
ARE ONLY FOR REFERENCE
DIGITAL VOLTMETER (Z > 1MOHM)
COLOUR BAR SIGNAL
AUDIO MONO 440HZ (VOLUME = 1/4 OF THE BARGRAPH)
MAGIC ORIGINAL
AV: MEASURED WITH SIGNAL APPLIED IN AV1
SUPPLY: 127Vac
IDENTIFICATION
ON TENSION
STAND BY: (tension)

* MODEL'S DIFERENCES

POS/MOD	CR14300	CR20300	CR20310
R802	NAO	6,67R	6,67R
J109	SIM	NAO	NAO
R698/9	8R2	8R2	3R9
R610	100R	100R	NAO
R608	2K2	2R8	
R609	3K3	3R9	
R715	3K3	1K8	
R716	1K2	1K8	
R721	10R	4,7R	
R723	10K	6K8	
R727	2K7	1K5	
R750/54	3K3	2k4	
R825A/835A	SIM	NAO	
R825/835	NAO	SIM	
R906	82K	47K	
J13	SIM	NAO	
CM852	NAO	SIM	
C434	1N7	4N7	1000F
C725	4N7	6N8	
C728	270N	470N	
C907	NAO	680PF	
C917	560PF	680PF	
T901	32H0E014901P	32080A5H89019	

ONLY FOR 20" STEREO

AUDIO OUTPUT

ONLY FOR 20" STEREO

AV1 REAR

AV2 FRONT

	SW 0	SW 1
AV1	0	5
AV2	5	5
TV	5	0

LIVE

COLD

GND - CLOSE TO TUNER

PINS FOR 20" CRT SOCKET (*)